



Power Strip CPPS*3-TT (EU)

IN: 1x powerCON TRUE1 TOP – OUT: 3x Schuko, 1x powerCON TRUE1 TOP

Power Strip is a reliable power distribution solution for indoor applications. Equipped with 1x powerCON® TRUE1® TOP In, up to 6x Schuko Outs and 1x powerCON® TRUE1® TOP Out for daisy chaining.

Features & Benefits

Highly reliable NEUTRIK® powerCON® recepticals for In and daisy chaining

Light weight, compact housing

Several mounting options

Market & applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Semi-permanent applications: Theaters, studios,..
- ✓ Permanent installations: Lecture hall, auditorium, classrooms,..

Article Variations

Article name	Details	Order code
CPPSF3-TT	IN: Power Strip with 1x powerCON® TRUE1® TOP - OUT: 3x Schuko Type F	1027441
CPPSE3-TT	IN: Power Strip with 1x powerCON® TRUE1® TOP - OUT: 3x Schuko Type E	1027596

Technical Information

Product	
Input device	powerCON® TRUE1® TOP CPPSF3-TT
Output device	CPPSE3-TT: 3 x Schuko Typ E
	CPPSF3-TT: 3 x Schuko Type F
Daisy chaining	1 x powerCON® True1® TOP

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical

Dimensions	272 x 60 x 46.6 mm
Conductor cross section	Daisy chaining: 2,5mm ² Schuko: 1,5mm ²
Weight	0.29 kg
Mounting options	mounting wholes

Material

Housing	PVC
Color	black

Environmental

Protection class	IP20
Temperature range	-5 °C to +40 °C