



Power Strip Multicore CPSMX-S2-B12

IN: 1x Socalpex 419 compatible – OUT: 12x NEMA 5-15/20R (Hubbell 5362), 1x Socalpex 419 compatible: 12x NEMA 5-15/20R (Hubbell 5362)

Power Strip Multicore are extremely rugged and compact distribution boxes which allow significant reduction of the cabling effort and cost due to the multicore inputs. It is ideally suited for demanding mobile applications. 2x Socalpex 419 compatible In – 12x NEMA 5-15/20R Out

COMING SOON!



Features & Benefits

- ✓ Reduction of cabling volume and effort due to Socalpex 419 compatible multipin Input / Daisy-chain.
- ✓ High mechanical protection: Rugged Easylen® housing with high IK, full connector protection with housing elements, high quality Hubbell NEMA 5-15/20 (Hubbell 5362)
- ✓ Very compact design: Height & Width only 96mm & 150mm due the stepped top plate.
- ✓ Easy transport & handling: stackable, lightweight, fully lockable. Options with the handle

on the request.

- ✓ Versatile mounting options: mounting wholes for pegs and suspension, truss clamp

Markets & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

Ordering information

Article name	Details	Order code
CPSMX-S2-B12	1x Socapex 419 compatible In– 12x NEMA 5-15/20R, 1x Socapex 419 compatible Out	1038766

Technical Information

Product	
Input device	1 x Socapex 419 compatible (6 channels)
Output device	12x NEMA 5-15/20R (Hubbell 5362)
Daisy chaining	1 x Socapex 419 compatible (6 channels)

Electrical	
Contact resistance / protection class Dielectric strength	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	20A

Mechanical

Dimensions	150 x 95,25 x 330mm
Weight	
Conductor cross section	AWG12
Mounting options	Truss clamp (M10), mounting holes for pegging or suspension
Type of construction	Stackable

Material

Housing	Easylen
Color	black

Environmental

Flammability acc. to UL 94	V0
Protection class	NEMA1 listing - pending. IP20
Temperature range	-25 °C bis +40 °C
Standard compliance	ETL Listing according to UL Standard 1640 – Pending