



Power Strip X CPSSX-T1-T6 (U.S.)

1x powerCON TRUE1 IN – 6x powerCON® TRUE1® TOP OUT - Indoor (NEMA1)

EU version: Power Strip X CPSX-T1-T6



Power Strip Xtreme (X) is a compact distribution solution for mobile applications. Rugged EASYLEN® housing is ideally suited for demanding applications and harsh conditions. 1x powerCON® TRUE1® TOP In and up to 6x powerCON® TRUE1® TOP Out.

COMING SOON!



Intertek

Features & Benefits

- Extreme robust and safe EASYLEN® housing with leather grain texture
- Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- Flame retardant (UL94-V0) and non-conductive housing material
- High mechanical protection (high IK)
- Light weight, compact
- Versatile mounting options

Market & Application

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

Ordering information

Article name	Details	Order code
CPSSX-T1-T6	IN: 1 x powerCON® TRUE1® TOP OUT: 6 x powerCON® TRUE1® TOP Indoor (NEMA1)	1035612

Technical Information

Product	
Input device	1x powerCON®TRUE1®TOP
Output device	6x powerCON®TRUE1®TOP
Daisy chaining	1x powerCON®TRUE1®TOP

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0.5 kV / mm
Rated voltage	120V AC
Rated Current	20A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical	
Lifetime	> 5000 Mating cycles per connector
Dimensions	380 x 91.2 x 76.7 mm
Conductor cross section	AWG12
Weight	1.0 kg
Mounting options	Truss clip, mounting wholes for pegging or suspension
Type of construction	Stackable

Material

Housing	Easylen
Color	black

Environmental

Standards compatibility	UL94-V0
Protection class	NEMA1 listed. IP20.
Temperature range	-25 °C bis +70°C

Compliance

Standard Compliance	ETL Listed. Compliant to UL STD 1640
----------------------------	--------------------------------------