




## Power Strip X CPSX-T1-T3 (EU)

1x powerCON TRUE1 IN – 3x powerCON® TRUE1® TOP  
OUT- Indoor (IP20)

US version: [Power Strip X CPSSX-T1-T3 USA](#)



Power Strip Xtreme (X) is a compact distribution solution for mobile applications. This distribution box is ideally suited for Indoor applications with restricted space / height and harsh usage conditions, for example in theaters, exhibition or similar applications. It also offers a very attractive price point.



## Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing with leather grain texture
- ✓ Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- ✓ Flame retardant (UL94-V2) and non-conductive housing material
- ✓ High mechanical protection (high IK)
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options
- ✓ Attractive price point



## Market & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events, exhibitions / trade shows
- ✓ Semi-permanent applications: Theaters, studios

## Ordering information

Article name	Details	Order code
CPSX-T1-T3	IN: 1 x powerCON® TRUE1® TOP OUT: 3 x powerCON® TRUE1® TOP Indoor (IP20)	1035599

## Technical Information

Product	
Input device	1x powerCON® TRUE1® TOP
Output device	3x powerCON® TRUE1® TOP
Daisy chaining	1x powerCON® TRUE1® TOP

Contact resistance / protection class	Protection class II
Dielectric strength	0.5 kV / mm
Rated voltage	16A (USA: 20A)
Rated Current	16A (USA: 20A)
Number of electrical contacts	2 + PE
Phases	single-phase

## Mechanical

Lifetime	> 5000 Mating cycles per connector
Dimensions	220 x 91.2 x 77 mm
Conductor cross section	2.08 mm <sup>2</sup>
Weight	0.55 kg
Mounting options	Truss clip, mounting wholes for pegging or suspension

## Material

Housing	Easylen
Color	black

## Environmental

Standards compatibility	UL94-V2
Protection class	IP20
Temperature range	-25 °C bis +70°C