

# Power Turtle X CPTX-T1-T7 (EU)

1 x powerCON TRUE1 TOP In- 7 x powerCON® TRUE1® TOP Out - Indoor (IP20)

US version: [Power Turtle X CPTSX-T1-T7 USA](#)



Power Turtle Xtreme Indoor (X) is a compact distribution solution for mobile applications. This distribution box is ideally suited for Indoor applications with restricted space / height and harsh usage conditions, for example in theaters, exhibition or similar applications. It also offers a very attractive price point.

## Features & Benefits

- Very compact, reduced height
- Extreme robust and safe EASYLEN® housing with leather grain texture
- Highly reliable NEUTRIK® powerCON® TRUE1® TOP receptacles for In, Out and Daisy chaining
- Flame retardant (UL94-V2) and non-conductive housing material
- High mechanical protection (high IK)
- Light weight, and stackable housing design
- Versatile mounting options
- Attractive price point

## Market & Application

- Markets. Professional video wall / lighting / audio
- Mobile application. Festivals, live events, exhibitions
- Semi-permanent applications. Theaters, studios

## Article order data

Article name	Details	Order code
CPTX-T1-T7	IN: powerCON® TRUE1® TOP OUT: 7x powerCON® TRUE1® TOP Indoor (IP20)	1035597

## Technical Information

Product	
Input device	1x powerCON® TRUE1® TOP
Output device	7x powerCON® TRUE1® TOP
Daisy chaining	1x powerCON® TRUE1® TOP

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0.5 kV / mm
Rated voltage	250V AC
Rated Current	16A (USA: 20A)
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical	
Lifetime	> 5000 mating cycles
Dimensions	220 x 150 x 65 mm
Conductor cross section	2,5 mm <sup>2</sup>
Weight	1.0 kg
Mounting options	Truss clamp, mounting wholes for pegging or suspension
Type of construction	Stackable

## Material

<b>Housing</b>	Easylen
<b>Color</b>	black

## Environmental

<b>Standards compatibility</b>	UL94-V2
<b>Protection class</b>	IP20
<b>Temperature range</b>	-25 °C to +70 °C