

# Power Bar XO NPBXOS-T1-T3 (EU+US)

COMING SOON!

Power Bar Xtreme Outdoor. 1x powerCON®TRUE1® IN  
– 3x powerCON®TRUE1® OUT

The Power Bar is an ultra-compact powerCON TRUE1 distribution box designed for professionals. Its innovative injection-molded housing offers exceptional ingress and mechanical protection, combined with high cost-efficiency. With a rugged, space-saving design, it is the ideal solution for demanding, harsh environments. 1x powerCON®TRUE1® and 3 x powerCON®TRUE1®



Power\_Bar\_XO\_NPBXOS-T1-T3\_(EU+US)



## Features & Benefits

- ✓ Ultra-compact injection-molded power distribution box for harsh applications
- ✓ High durability and safety: Impact-resistant (high IK rating), non-conductive, flame-retardant polymer housing (V0)
- ✓ Outdoor-ready: IP65 protection, self-closing caps, UV-resistant material (UL 746C F1 certified), high temperature resistance, high impact strength
- ✓ Flexible mounting options: powerBAR truss clips, screw and Velcro strap mounting holes
- ✓ Attractive pricing

## Market & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

## Article Variations

Article name	Details	Order code
NPBXOS-T1-T3	IN: 1x powerCON®TRUE1® -OUT: 3 x powerCON®TRUE1®	1041280

## Technical Information

Product	
<b>Input device</b>	1x powerCON®TRUE1®TOP with self-closing caps
<b>Output device</b>	3x powerCON®TRUE1®TOP with self-closing caps

Electrical	
<b>Contact resistance / protection class</b>	Protection class II
<b>Dielectric strength</b>	0.5 kV / mm
<b>Rated Voltage and Current</b>	CE: 16 A, 250 VAC; UL: 20 A, 250 VAC
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Lifetime</b>	> 5000 Mating cycles per connector
<b>Mechanical impact resistance</b>	IK9
<b>Dimensions</b>	245 x 60 x 69 mm
<b>Conductor cross section</b>	AWG12
<b>Weight</b>	0.65 kg
<b>Mounting options</b>	Truss clip and mounting holes for securing or suspending with screws or Velcro

**Material**

**Housing** Polymer composite

**Color** black

**Environmental**

**Standards compatibility** UL94-V0

**Standard compliance** ETL Listing according to UL Standard 1640 – Pending

**Protection class** IP65 / NEMA3R

**Temperature range** -25 °C bis +70°C