



CCV5RD

Outdoor Power Strip XO with 6 powerCON® TRUE1® TOP out sockets in rugged EASYLEN® housing for harsh environment. Equipped with 3-phase input connector for higher power consumption. Ideally suited for outdoor usage and under harsh conditions.

Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing, flame retardant material (UL94 V2)
- ✓ IP 65 rated / IK 10+ rated (impact resistant)
- ✓ Mounting options / truss clip / truss clamp
- ✓ Reliable NEUTRIK® powerCON® TRUE1® TOP recepticals
- ✓ Self closing caps
- ✓ Daisy chaining
- ✓ Light weight and compact design

Article Variations

Article name	Details	Order code
CCV5RD-6T1-C	6x powerCON® TRUE1® TOP with CEE16-5 In IP65 Power Strip XO	1027454
CCV5RD-6T1-2C	6x powerCON® TRUE1® TOP with CEE16-5 In and Out IP65 Power Strip XO	1027455

Technical Information

Product	
Input device	CEE16-5 CCV5RD-6T1-C CEE16-5 CCV5RD-6T1-2C
Output device	6x powerCON® TRUE1® TOP CCV5RD-6T1-C 6x powerCON® TRUE1® TOP with CEE16-5 CCV5RD-6T1-2C
Design	Mobile / portable

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A (USA: 20A)
Number of electrical contacts	4 + PE
Phases	multi-phase (3+N+PE)

Mechanical

Dimensions	489,6 x 92 x 117,2mm CCV5RD-6T1-C
	528,6 x 92 x 117,2mm CCV5RD-6T1-2C
Conductor cross section	2,5mm ²

Material

Housing	Easylen
Color	black

Environmental

Standards compatibility	UL94-V2
Protection class	IP65
Temperature range	-25 °C to +80 °C

Mobile cable

Weight	1,9kg CCV5RD-6T1-C
	2,1kg CCV5RD-6T1-2C