

CP-PM

cPot recessed male connectors



cPot recessed male connector is a solution for the integration of the cPot receptacle into the device enclosure or panel.

Features & Benefits

- cPot recessed male connectors is a solution for the integration in the device enclosure or panel installation

Article Variations

Article name	Details	Order name
CP-PMA	Panel male PE axial 10-25 mm ²	1027373
CP-PMB	Panel male PE terminal block 2x35/1x25 mm ²	1027374
CP-PM620	Panel male PE M6x20 mm	1027375

Technical Information

Product	
Description	CP-PMx
Scope of delivery	CP-PMA: 1x panel housing male green, 1x insert male yellow, 1x axial contact 10-25mm ² male, 13mm isolation of cable has to be removed
	CP-PMB: Panel male PE terminal block 2x35/1x25 mm ²
	CP-PM620: 1x panel housing male green, 1x insert male yellow, 1x contact male with M6 thread 20mm

Electrical	
Contactor resistance	≤0,3 mΩ

Mechanical	
Lifetime	> 500 Mating cycles per connector
Locking device	Latch lock
Conductor cross section	16 mm ² , 25 mm ²

Material	
Contact	1 contact, copper alloy
Shell	Polycarbonat (PC)

Environmental

Standards compatibility	UL94-V0 (connector)
Protection class nach IEC 60529	IP65 in mated condition
Temperature range	-40 °C – 55°C