




Power Turtle XO CPTS-T1-T7 (U.S.)

Power Turtle Xtreme Outdoor. 1 x powerCON TRUE1 TOP In- 7 x powerCON® TRUE1® TOP Out.

Power Turtle Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions.

COMING SOON!



Features & Benefits

- ✓ Extreme robust EASYLEN® housing (high IK) with leather grain texture
- ✓ Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- ✓ Flame retardant (UL94-V0) and non-conductive housing material



- ✓ High outdoor protection (IP65)
- ✓ Additional connector protection positioning NEUTRIK® powerCON® TRUE1® TOP and protruding housing tiles
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

Market & Application

- ✓ Markets. Professional video wall / lighting / audio
- ✓ Mobile application. Festivals, live events
- ✓ Semi-permanent applications. Theaters, studios

Article order data

Article name	Details	Order code
CPTS-T1-T7	IN: powerCON® TRUE1® TOP - OUT: 7x powerCON® TRUE1® TOP	1038772

Technical Information

Product	
Input device	1x powerCON® TRUE1® TOP with self-closing caps
Output device	7x powerCON® TRUE1® TOP with self-closing caps
Daisy chaining	1x powerCON® TRUE1® TOP with self-closing caps

Electrical

Contact resistance / protection class	Protection class II
Dielectric strength	0.5 kV / mm
Rated voltage	250V AC
Rated Current	20A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical

Lifetime	> 5000 Mating cycles
Dimensions	220 x 150 x 85 mm
Conductor cross section	AWG12
Weight	1.18 kg
Mounting options	Truss clamp, mounting wholes for pegging or suspension
Type of construction	Stackable

Material

Housing	Easylen
Color	black

Environmental

Standard compliance	ETL Listing according to UL Standard 1640 – Pending
Protection class	NEMA3R listing - pending. IP20.
Temperature range	-25 °C to +70 °C

