


Power Turtle XO

CPVT7RT

Power Turtle Xtreme Outdoor. 1 x powerCON TRUE1
TOP In- 7 x powerCON® TRUE1® TOP Out.

Power Turtle Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions.



Features & Benefits

- Extreme robust EASYLEN® housing (high IK) with leather grain texture
- Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- Flame retardant (UL94-V2) and non-conductive housing material
- High outdoor protection (IP65)
- Additional connector protection positioning NEUTRIK® powerCON® TRUE1® TOP and protruding housing tiles
- Light weight, compact and stackable housing design
- Versatile mounting options

Market & Application

- Markets. Professional video wall / lighting / audio
- Mobile application. Festivals, live events
- Semi-permanent applications. Theaters, studios

Article order data

| Article name | Details | Order code |
|--------------|---|------------|
| CPVT7RT | IN: powerCON® TRUE1® TOP - OUT: 7x powerCON® TRUE1® TOP | 1027451 |

Technical Information

| Product | |
|-----------------------|--|
| Input device | 1x powerCON® TRUE1® TOP with self-closing caps |
| Output device | 7x powerCON® TRUE1® TOP with self-closing caps |
| Daisy chaining | 1x powerCON® TRUE1® TOP with self-closing caps |

| Electrical | |
|--|---------------------|
| Contact resistance / protection class | Protection class II |
| Dielectric strength | 0.5 kV / mm |
| Rated voltage | 250V AC |
| Rated Current | 16A (USA: 20A) |
| Number of electrical contacts | 2 + PE |
| Phases | single-phase |

| Mechanical | |
|--------------------------------|--|
| Lifetime | > 5000 Mating cycles |
| Dimensions | 220 x 150 x 85 mm |
| Conductor cross section | 2,5 mm ² |
| Weight | 1.18 kg |
| Mounting options | Truss clamp, mounting wholes for pegging or suspension |
| Type of construction | Stackable |

Material

| | |
|----------------|---------|
| Housing | Easylen |
| Color | black |

Environmental

| | |
|--------------------------------|------------------|
| Standards compatibility | UL94-V2 |
| Protection class | IP65 |
| Temperature range | -25 °C to +70 °C |