



Power Container Xtreme Outdoor CPC63-C1- C4T3F3-RBM

On request modification.

Power Container is a highly reliable, rugged and first level powerful distribution solution.

Features & Benefits

- ✓ **High durability & protection:** rugged Easylen® housing with high IK, IP44 with all connectors in mated condition, self-closing caps, connector protection, flame retardant & non-conductive housing material
- ✓ **Easy transport & handling:** compact, stackable, fully lockable, integrated handles
- ✓ **High quality of component and assembly** add to high reliability and safety of the power distribution and the event

- ✓ Markets: LED walls, Lighting, Other
- ✓ Mobile applications: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios, fairs

Order information

Product title	Details	Order code
CPC63-C1-C4T3F3-RBM	Please see the drawing and technical information below.	1038187

Technical Information

Product	
Input device	1x CEE63A 5P red
Output device	2x CEE 32A 5P (2x MCB32A C 3P, 2x RCCB 40A 30mA 4P) 2x CEE 16A 5P (2x MCB32A C 3P, 2x RCCB 40A 30mA 4P) 3x PowerCON TRUE1 TOP & 3x Schuko F Type (6x MCB16A C 1P, 1x RCCB 40A 30mA 4P) 1x cPot
Main switch	4pol
Power meter	Selec MFM 384

Phase control indicator	L1, L2, L3, green
Rated voltage	415V/AC, 50Hz
Rated Current	In: 63A

Mechanical

Type of construction	Stackable
Dimensions	ca. 395 x 295 x 405 mm

[illegible]

Housing	Easylen®
Color	black

Environmental

Protection class	IP44 with CEE and cPot in mated condition
Temperature range	-5 °C to +40 °C