

Power Rack Xtreme

CPR32-C2-F7-CB

1x CEE32A In / Daisy chain – 7 x Schuko Typ F Out.

Power Rack Xtreme is a powerful and highly reliable distribution solution for installation in the 19" Rack. It is ideally suited for amplifier rack wiring application.



Features & Benefits

- High quality electrical and electronical component from the renowned brands
- Circuit protection with residual current device (RCCB) and miniature circuit breakers (MCB)
- High quality assembly in EU
- Attractive price / value ratio

Markets & Applications

- Markets: Professional audio esp. amp rack wiring / lighting / video wall
- Mobile applications: Festivals, live events. Control panels / rooms.
- Semi-permanent applications: Theaters, studios, fairs. Control panels /rooms.

Ordering information

| Article name | Details | Order code |
|----------------|---|------------|
| CPR32-C2-F7-CB | FRONT: IN 1x CEE32A; Daisy chain 1x CEE32A; OUT 1x Schuko Type F; Circuit protection: 1x RCCB, 3x MCB. BACK: OUT 6x Schuko Type F | 1028798 |

Technical Information

| Product | |
|----------------------|--------------------------------------|
| Input device | 1x CEE32A 5P red (front) |
| Daisy chain | 1x CEE32A 5P red (daisy chain) front |
| Output device | 7x Schuko socket with lid |

| Electrical | |
|--------------------------------|---|
| Circuit protection | 1x RCCB 40/0,03A 3x MCB 1pol C16 |
| Phase control indicator | L1, L2, L3, green |
| Rated voltage | 415V/AC, 50Hz |
| Rated Current | CEE socket: 415V Link Schuko socket 230V 16A |

| Mechanical | |
|-----------------------------|--------------------------------------|
| Weight | 3,8kg |
| Type of construction | 19" Housing 2 HE, 1,5TE |
| Dimensions | 483 x 88 x 104 mm (without fittings) |

| Material | |
|----------------|-------|
| Housing | Metal |
| Color | black |

Environmental

| | |
|--------------------------|-------------|
| Protection class | IP20 |
| Temperature range | -5 to +40°C |