




# Power Rack Xtreme

## CPR32-C2-F9-CB

1x CEE32A In / Daisy chain, 9x Schuko Type F Out

Power Rack Xtreme is a powerful and highly reliable distribution solution for installation in the 19" Rack. It is ideally suited for amplifier rack wiring application.



## Features & Benefits

- High quality electrical and electronical component from the renowned brands
- Circuit protection with residual current device (RCCB) and miniature circuit breakers (MCB)
- High quality assembly in EU
- Attractive price / value ratio

## Markets & Applications

- Markets: Professional audio esp. amp rack wiring / lighting / video wall
- Mobile application: Festivals, live events. Control panels / rooms.
- Semi-permanent applications: Theaters, studios, fairs. Control panels /rooms.

## Ordering information

| Article name   | Details  |
|----------------|--|
| CPR32-C2-F9-CB | Front: IN 1x CEE32A; Daisy chain 1x CEE32A; OUT 3x Schuko Type F; Circuit protection: 3x MCB.<br>Back: OUT6x Schuko Type F |

## Technical Information

| Product              |  |
|----------------------|--|
| <b>Input device</b>  | 1x CEE32A 5P red (front)                 |
| <b>Daisy chain</b>   | 1x CEE32A 5P red (daisy chain) front     |
| <b>Output device</b> | 9x Schuko Type F socked with lid (front) |

| Electrical                     |  |
|--------------------------------|--|
| <b>Circuit protection</b>      | 3x MCB 1pol C16                                |
| <b>Phase control indicator</b> | L1, L2, L3, green                              |
| <b>Rated voltage</b>           | 415 V/AC, 50 Hz                                |
| <b>Rated current</b>           | CEE Socket: 415 V<br>Schuko Socket: 230 V 16 A |

| Mechanical                  |                                      |
|-----------------------------|--------------------------------------|
| <b>Weight</b>               | 3.8 kg                               |
| <b>Type of construction</b> | 19" Housing 2 HE, 1.5 TE             |
| <b>Dimensions</b>           | 483 x 88 x 104 mm (without fittings) |

| Material       |       |
|----------------|-------|
| <b>Housing</b> | Metal |
| <b>Color</b>   | Black |

| Environmental            |             |
|--------------------------|-------------|
| <b>Protection class</b>  | IP20        |
| <b>Temperature range</b> | -5 to +40°C |

