

POWER RACK XTREME CPRX63-C1-H4T6-ROM

On request modification.

IN: Input cable 2m 1x CEE63A, OUT: 4x Harting E16, 6x powerCON TRUE1 TOP.

Power Rack Xtreme is a powerful and highly reliable distribution solution for installation in the 19" Rack. It is ideally suited for amplifier rack wiring application.

Features & Benefits

- High quality electrical and electronical component from the renowned brands
- Circuit protection with residual current device (RCCB) and miniature circuit breakers (MCB)
- High quality assembly in EU
- Attractive price / value ratio

 \bigcirc

C

0 00



- ✓ Markets: Professional audio esp. amp rack wiring / lighting / video wall
- ✓ Mobile applications: Festivals, live events. Control panels / rooms.
- ✓ Semi-permanent applications: Theaters, studios, fairs. Control panels /rooms.

Ordering information

| Article name | Details | Order code |
|------------------------|--|------------|
| CPRX63-C1-H4T6- ROM | Front: 24x RCBO (1-pole+N), 1x measuring device Selec MFM 384, 1x main switch 4-pin, Back: IN: 1x Input cable 2m with CEE63A, OUT: 4x Harting E16, 6x powerCON TRUE1 TOP | 1038252 |

Technical Information

| Product | |
|---------------|---|
| Input device | IN: 1x Input cable 2m with CEE63A |
| Daisy chain | |
| Output device | 4x Harting E16 6ch [1-9] 24x RCBO (1-pole+N) 6x powerCON TRUE1 TOP (parallel to Harting 1) 1x cPot |
| Main switch | 1x main switch 4-pin |
| Power meter | 1x Selec MFM 384 |

| LICULIICAI | |
|-------------------------|------|
| Phase control indicator | |
| Rated voltage | 400V |
| Rated Current | 63A |

| Mechanical | |
|----------------------|------------------|
| Weight | |
| Type of construction | 19" Housing 6 HE |

| Material | |
|----------|-------|
| Housing | Metal |
| Color | Black |

| Environmental | |
|-------------------|-------------|
| Protection class | IP20 |
| Temperature range | -5 to +40°C |