

Power Strip CPPS*6-TT

IN: 1x powerCON TRUE1 TOP IN – OUT: 6 x Schuko, 1x powerCON TRUE1 TOP



Power Strip is a reliable power distribution solution for indoor applications. Equipped with 1x powerCON® TRUE1® TOP IN, up to 6x Schuko OUT and 1x powerCON® TRUE1® TOP OUT for daisy chaining.

Features & Benefits

Highly reliable NEUTRIK® powerCON® recepticals for In and daisy chaining

Light weight, compact housing

Several mounting options

Market & applications

- Markets: Professional video wall / lighting / audio
- Permanent installations: Lecture hall, auditorium, classrooms,..
- Semi-permanent applications: Theaters, studios,..

Article Variations

| Article name | Details |
|--------------|---|
| CPPSF6-TT | IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type F OUT and 1x powerCON® TRUE1® TOP |
| CPPSE6-TT | IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type E OUT and 1x powerCON® TRUE1® TOP |

Technical Information

| Product | |
|----------------|---|
| Input device | 1 x powerCON® TRUE1® TOP |
| Output device | CPPSE6-TT: 6x Schuko Typ E CPPSF6-TT: 6x Schuko Type F |
| Daisy chaining | 1x powerCON® TRUE1® TOP |

| Electrical | |
|---------------------------------------|---------------------|
| Contact resistance / protection class | Protection class II |
| Dielectric strength | 0,5 kV / mm |
| Rated voltage | 250V AC |
| Rated Current | 16A |
| Number of electrical contacts | 2 + PE |
| Phases | single-phase |

| Mechanical | |
|-------------------------|--|
| Dimensions | 398 x 60 x 46.6 mm |
| Conductor cross section | Daisy chaining: 2.5 mm ² Schuko; 1.5 mm ² |
| Weight | 0.43 kg |
| Mounting options | mounting wholes |

| Material | |
|----------|-------|
| Housing | PVC |
| Color | black |

Environmental

| | |
|--------------------------|------------------|
| Protection class | IP20 |
| Temperature range | -5 °C bis +40 °C |