

Power Strip CPPS*6-TT (EU)

IN: 1x powerCON TRUE1 TOP IN – OUT: 6 x Schuko, 1x powerCON TRUE1 TOP



Power Strip is a reliable power distribution solution for indoor applications. Equipped with 1x powerCON® TRUE1® TOP IN, up to 6x Schuko OUT and 1x powerCON® TRUE1® TOP OUT for daisy chaining.

Features & Benefits

Highly reliable NEUTRIK® powerCON® recepticals for In and daisy chaining

Light weight, compact housing

Several mounting options

Market & applications

- Markets: Professional video wall / lighting / audio
- Semi-permanent applications: Theaters, studios,..
- Permanent installations: Lecture hall, auditorium, classrooms,..

Article Variations

Article name	Details
CPPSF6-TT	IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type F OUT and 1x powerCON® TRUE1® TOP
CPPSE6-TT	IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type E OUT and 1x powerCON® TRUE1® TOP

Technical Information

Product	
Input device	1 x powerCON® TRUE1® TOP
Output device	CPPSE6-TT: 6x Schuko Typ E CPPSF6-TT: 6x Schuko Type F
Daisy chaining	1x powerCON® TRUE1® TOP

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical	
Dimensions	398 x 60 x 46.6 mm
Conductor cross section	Daisy chaining: 2.5 mm ² Schuko; 1.5 mm ²
Weight	0.43 kg
Mounting options	mounting wholes

Material	
Housing	PVC
Color	black

Environmental

Protection class	IP20
Temperature range	-5 °C bis +40 °C