



Power Strip XO CPPS3RD-TT (EU)

Power Strip Xtreme Outdoor. 1x

powerCON®TRUE1®TOP IN - 3xSchuko Type E / F & 1x

powerCON®TRUE1®TOP OUT

Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile applications. Rugged EASYLEN®housing is ideally suited for demanding applications under harsh conditions. 1x powerCON®TRUE1®TOP In and up to 6x Schuko Type E / F Out & 1x powerCON®TRUE1®TOP Out

Features & Benefits

- ✓ Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for IN and daisy chaining, Mains receptacles Schuko Type E/F
- ✓ Flame retardant (UL94-V0) and non-conductive housing material
- ✓ High outdoor protection (IP54, IK, ..)
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

Market & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

Article Variations

Article name	Details	Order code
CPPSE3RD-TT	IN: 1 x powerCON® TRUE1® TOP - OUT: 3 x Schuko Type E	1027604
CPPSF3RD-TT	IN: 1 x powerCON® TRUE1® TOP - OUT: 3 x Schuko Type F	1027449

Technical Information

Product	
Input device	1x powerCON® TRUE1® TOP
Output device	CPPSE3RD-TT: 3x Schuko Type E with self-closing caps
	CPPSF3RD-TT: 3x Schuko Type F with self-closing caps
Daisy chaining	1x powerCON® TRUE1® TOP with self-closing caps

Electrical

Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A (USA: 20A)
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical

Dimensions	224,7 x 77 x 100,6mm
Conductor cross section	2,5 mm ²
Weight	0.72 kg
Mounting options	Truss clip, mounting wholes for pegging or suspension

Material

Housing	Easylen
Color	black

Environmental

Standards compatibility	UL94-V0
Protection class	IP54
Temperature range	-25 °C to +70 °C