



Power Strip XO CPPSE6RD-TT

Power Strip Xtreme Outdoor. 1 x
powerCON®TRUE1®TOP IN - 6 x Schuko Type E / F &
1x powerCON®TRUE1®TOP OUT

Power Strip Xtreme Outdoor (XO) is a compact
distribution solution for mobile applications. Rugged
EASYLEN®housing is ideally suited for demanding
applications under harsh conditions. 1 x
powerCON®TRUE1®TOP In and up to 6 x Schuko Type
E / F Out & 1x powerCON®TRUE1®TOP Out

Features & Benefits

- Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In and daisy chaining, Mains receptacles Schuko Type E/F
- Flame retardant (UL94-V2) and non-conductive housing material
- High outdoor protection (IP54, IK, ..)
- Light weight, compact and stackable housing design
- Versatile mounting options

Market & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

Article Variations

| Article name | Details | Order code |
|--------------|---|------------|
| CPPSE6RD-TT | IN: 1 x powerCON® TRUE1® TOP - OUT: 6 x Schuko Type E | 1027605 |
| CPPSF6RD-TT | IN: 1 x powerCON® TRUE1® TOP - OUT: 6 x Schuko Type F | 1027450 |

Technical Information

| Product | |
|-----------------------|--|
| Input device | 1x powerCON® TRUE1® TOP |
| Output device | CPPSE6RD-TT: 6x Schuko Type E with self-closing caps |
| | CPPSF6RD-TT: 6x Schuko Type F with self-closing caps |
| Daisy chaining | 1x powerCON®TRUE1®TOP with self-closing caps |

| Electrical | |
|--|---------------------|
| Contact resistance / protection class | Protection class II |
| Dielectric strength | 0,5 kV / mm |
| Rated voltage | 250V AC |
| Rated Current | 16 A |
| Number of electrical contacts | 2 + PE |
| Phases | single-phase |

| Mechanical | |
|--------------------------------|---|
| Dimensions | 384.7 x 77 x 100.6mm |
| Conductor cross section | 2,5mm ² |
| Weight | 1.25 kg |
| Mounting options | Truss clip, mounting wholes for pegging or suspension |

Material

| | |
|----------------|---------|
| Housing | Easylen |
| Color | black |

Environmental

| | |
|--------------------------------|------------------|
| Standards compatibility | UL94-V2 |
| Protection class | IP54 |
| Temperature range | -25 °C bis +70°C |