



Power Strip XO NPSSXO-T1-T6 (U.S.)

Power Strip Xtreme Outdoor. 1x powerCON TRUE1 IN – 6x powerCON® TRUE1® TOP OUT

Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions. 1x powerCON® TRUE1® TOP In and up to 6x powerCON® TRUE1® TOP Out.

COMING SOON!

Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing with leather grain texture
- ✓ Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- ✓ Flame retardant (UL94-V0) and non-conductive housing material
- ✓ High outdoor protection (IP65, IK, ..)
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

Market & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

Article Variations

Article name	Details	Order code
NPSSXO-T1-T6	IN: 1 x powerCON® TRUE1® TOP - OUT: 6 x powerCON® TRUE1® TOP	1038771

Technical Information

Product	
Input device	1x powerCON®TRUE1®TOP with self-closing caps
Output device	6x powerCON®TRUE1®TOP with self-closing caps
Daisy chaining	1x powerCON®TRUE1®TOP with self-closing caps

Electrical

Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	20A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical

Lifetime	> 5000 Mating cycles per connector
Dimensions	380 x 91.2 x 77 mm
Conductor cross section	AWG12
Weight	1.15 kg
Mounting options	Truss clip, mounting holes for pegging or suspension

Material

Housing	Easylen
Color	black

Environmental

Standard compliance	ETL Listing according to UL Standard 1640 – Pending
Protection class	NEMA3R listing - pending. IP20.
Temperature range	-25 °C to +70 °C