



## Power Turtle Xtreme Outdoor CPTM-H1-T6 (EU)

IN: 1x Harting E16 – OUT: 6x powerCON<sup>®</sup> TRUE1<sup>®</sup>  
TOP

Power Turtle Multicore are extremely rugged compact distribution boxes which allow significant reduction of the cabling volume, effort and cost due to the multicore input. It is ideally suited for outdoor usage and demanding mobile applications. 1x Harting E16 In – 6x powerCON<sup>®</sup> TRUE1<sup>®</sup> TOP Out

## Features & Benefits

- **Reduction of cabling volume and effort** due to Harting E16 multipin connectors. And Even more reduction of cabling due to the versions with 12x Outs
- **High durability & protection:** Rugged Easylen® housing with high IK, IP65 with Harting E16 in mated condition, self-closing caps, lateral connector arrangement, flame retardant & non-conductive housing material
- **Very compact design:** flat design, lateral connector arrangement, applications with restricted space.
- **Easy transport & handling:** stackable with other Power Turtles, lightweight, fully lockable
- **Versatile mounting options:** pegs, suspension, truss clamp

## Markets & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

## Ordering information

Article name	Details	Order code
CPTM-H1-T6	IN: 1x Harting E16, £ OUT: 6x powerCON T1 TOP	1028228

## Technical Information

Product	
<b>Input device</b>	1x Harting E 16 (6 channels) [1-9]
<b>Output device</b>	6x powerCON® TRUE1® TOP with self-closing caps
<b>Daisy chaining</b>	powerCON® TRUE1® TOP with self-closing caps

Electrical	
<b>Contact resistance / protection class Dielectric strength</b>	Protection class II
<b>Dielectric strength</b>	0,5 kV / mm
<b>Rated voltage</b>	250V AC
<b>Rated Current</b>	16A
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Dimensions</b>	225 x 173 x 87 mm
<b>Weight</b>	1,3 kg
<b>Conductor cross section</b>	2,08 mm <sup>2</sup>
<b>Mounting options</b>	Truss clamp (M10), mounting wholes for pegging or suspension
<b>Type of construction</b>	Stackable

## Material

<b>Housing</b>	Easylen
<b>Color</b>	black

## Environmental

<b>Flammability acc. to UL 94</b>	V-2
<b>Protection class</b>	IP65 with Harting E16 in mated condition
<b>Temperature range</b>	-25 °C bis +40 °C