



Power Turtle Xtreme Outdoor CPTM-H1-T6

IN: 1x Harting E16 – OUT: 6x powerCON® TRUE1®
TOP

Power Turtle Multicore are extremely rugged compact distribution boxes which allow significant reduction of the cabling volume, effort and cost due to the multicore input. It is ideally suited for outdoor usage and demanding mobile applications. 1x Harting E16 In – 6x powerCON® TRUE1® TOP Out

Features & Benefits

- **Reduction of cabling volume and effort** due to Harting E16 multipin connectors. And Even more reduction of cabling due to the versions with 12x Outs
- **High durability & protection:** Rugged Easylen® housing with high IK, IP65 with Harting E16 in mated condition, self-closing caps, lateral connector arrangement, flame retardant & non-conductive housing material
- **Very compact design:** flat design, lateral connector arrangement, applications with restricted space.
- **Easy transport & handling:** stackable with other Power Turtles, lightweight, fully lockable
- **Versatile mounting options:** pegs, suspension, truss clamp

Markets & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

Ordering information

Article name	Details	Order code
CPTM-H1-T6	IN: 1x Harting E16, £ OUT: 6x powerCON T1 TOP	1028228

Technical Information

Product	
Input device	1x Harting E 16 (6 channels) [1-9]
Output device	6x powerCON® TRUE1® TOP with self-closing caps
Daisy chaining	powerCON® TRUE1® TOP with self-closing caps

Electrical	
Contact resistance / protection class Dielectric strength	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical	
Dimensions	225 x 173 x 87 mm
Weight	1,3 kg
Conductor cross section	2,08 mm ²
Mounting options	Truss clamp (M10), mounting wholes for pegging or suspension
Type of construction	Stackable

Material

Housing	Easylen
Color	black

Environmental

Flammability acc. to UL 94	V-2
Protection class	IP65 with Harting E16 in mated condition
Temperature range	-25 °C bis +40 °C