



## Power Turtle Xtreme Outdoor CPTM-S1-T6

IN: 11x Socapex 419 – OUT: 6x powerCON<sup>®</sup> TRUE1<sup>®</sup>  
TOP

Power Turtle Multicore are extremely rugged compact distribution boxes which allow significant reduction of the cabling volume, effort and cost due to the multicore input. It is ideally suited for outdoor usage and demanding mobile applications.

## Features & Benefits

- **Reduction of cabling volume and effort** due to Socapex 419 compatible multipin connector. And Even more reduction of cabling due to the versions with 12x Outs
- **High durability & protection:** Rugged Easylen® housing with high IK, IP65 with Socapex 419 in mated condition, self-closing caps, lateral connector arrangement, flame retardant & non-conductive housing material
- **Very compact design:** flat design, lateral connector arrangement, applications with restricted space.
- **Easy transport & handling:** stackable with other Power Turtles, lightweight, fully lockable
- **Versatile mounting options:** pegs, suspension, truss clamp

## Markets & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

## Ordering information

Article name	Details	Order code
CPTM-S1-T6	IN: 1x Socapex 419 compatible OUT: 6x powerCON TRUE1 TOP	1028858

## Technical Information

Product	
<b>Input device</b>	1x Socapex 419 compatible (6 channels)
<b>Output device</b>	6x powerCON® TRUE1® TOP with self-closing caps
<b>Daisy chaining</b>	powerCON® TRUE1® TOP with self-closing caps

Electrical	
<b>Contact resistance / protection class</b>	Protection class II
<b>Dielectric strength</b>	0,5 kV / mm
<b>Rated voltage</b>	250V AC
<b>Rated Current</b>	16A
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Dimensions</b>	225 x 166 x 87mm
<b>Weight</b>	1,4 kg
<b>Conductor cross section</b>	2,08 mm <sup>2</sup>
<b>Mounting options</b>	Truss clamp (M10), mounting wholes for pegging or suspension
<b>Type of construction</b>	Stackable

Material	
<b>Housing</b>	Easylen
<b>Color</b>	black

## Environmental

<b>Flammability acc. to UL 94</b>	V-2
<b>Protection class</b>	IP65 with Socapex 419 in mated condition
<b>Temperature range</b>	-25 °C bis +40 °C